

# Product datasheet

Specifications



## Acti9 - IC2000 - twilight switch - 2...2000 lux

CCT15284

! Discontinued on: 31 May 2019

! End-of-service on: 2 Oct 2020

! Discontinued

EAN Code: 3606480179532

### Main

Range Of Product	Acti9
Product Name	Acti9 IC
Product Or Component Type	Twilight switch
Device Short Name	IC2000
Provided Equipment	switchboard cell
Load Type	230 V AC halogen lamp: 2300 W 230 V AC incandescent lamp: 2300 W dual mounted fluorescent tube with conventional ballast: 2300 VA dual mounted fluorescent tube with electronic ballast: 300 VA fluocompact lamp with conventional ballast: 1500 VA non-corrected fluorescent tube with conventional ballast: 2300 VA parallel-corrected fluorescent tube with conventional ballast: 400 VA parallel-corrected mercury and sodium vapour lamps: 400 VA serial-corrected fluorescent tube with conventional ballast: 2300 VA 7 x 11 W fluocompact lamp with electronic ballast 7 x 15 W fluocompact lamp with electronic ballast 7 x 20 W fluocompact lamp with electronic ballast 7 x 23 W fluocompact lamp with electronic ballast 9 x 7 W fluocompact lamp with electronic ballast
Function Available	Cabling test function with a push-button on front face

### Complementary

Device Application	Building
Number Of Channels	1
Power Consumption In Va	6 VA
[Ue] Rated Operational Voltage	230 V AC +10 % -15 % at 50/60 Hz
Maximum Switching Current	10 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1
Electrical Insulation Class	Class II
Opening Distance	< 3 mm
Status Led	LED (green) threshold reached LED (red) brightness less than the threshold
Time Delay	>= 60 s on closing >= 60 s on breaking contact
9 Mm Pitches	5
Light Intensity Adjustment	2...2000 lux
Connections - Terminals	2 x 2.5 mm <sup>2</sup> screwless terminals
Height	85 mm

<b>Width</b>	45 mm
<b>Depth</b>	65 mm
<b>Net Weight</b>	280 g
<b>Control Type</b>	By brightness detection
<b>Market Segment</b>	Small commercial Residential
<b>Compatibility Code</b>	IC2000

## Environment

<b>Ambient Air Temperature For Operation</b>	-25...50 °C
<b>Ip Degree Of Protection</b>	IP20 B
<b>Standards</b>	EN 60669 EN 60529

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	9 cm
<b>Package 1 Width</b>	9 cm
<b>Package 1 Length</b>	11 cm
<b>Package 1 Weight</b>	308 g

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

RoHS Exemption Information Yes

## Certifications & Standards

**Eu RoHS Directive** Pro-active compliance (Product out of EU RoHS legal scope)  
[EU RoHS Declaration](#)

**China RoHS Regulation** [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

**Environmental Disclosure** [Product Environmental Profile](#)

**Circularity Profile** [End of Life Information](#)