

Product datasheet

Specifications



Acti9 - IC2000 - twilight switch - 2â€¦2000 lux

CCT15368

! Discontinued on: Sep 4, 2023

! To be end-of-service on: Sep 3, 2026

! Discontinued

Main

Range Of Product	Acti9
Product Name	Acti9 IC
Product Or Component Type	Twilight switch
Device Short Name	IC2000
Provided Equipment	wall-mounted cell
Load Type	230 V AC halogen lamp: 2300 W 230 V AC incandescent lamp: 2300 W dual mounted fluorescent tube with conventional ballast: 2300 VA dual mounted fluorescent tube with electronic ballast: 300 VA fluocompact lamp with conventional ballast: 1500 VA non-corrected fluorescent tube with conventional ballast: 2300 VA parallel-corrected fluorescent tube with conventional ballast: 400 VA parallel-corrected mercury and sodium vapour lamps: 400 VA serial-corrected fluorescent tube with conventional ballast: 2300 VA 7 x 11 W fluocompact lamp with electronic ballast 7 x 15 W fluocompact lamp with electronic ballast 7 x 20 W fluocompact lamp with electronic ballast 7 x 23 W fluocompact lamp with electronic ballast 9 x 7 W fluocompact lamp with electronic ballast
Function Available	Cabling test function with a push-button on front face

Complementary

Device Application	Building
Number Of Channels	1
Power Consumption In Va	6 VA
[Ue] Rated Operational Voltage	230 V AC +10 % -15 % at 50/60 Hz
Maximum Switching Current	10 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1
Electrical Insulation Class	Class II
Opening Distance	< 3 mm
Status Led	LED (green) threshold reached LED (red) brightness less than the threshold
Time Delay	>= 60 s on closing >= 60 s on breaking contact
9 Mm Pitches	5
Light Intensity Adjustment	2...2000 lux
Connections - Terminals	2 x 2.5 mm ² screwless terminals
Height	85 mm

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Width	45 mm
Depth	65 mm
Net Weight	280 g
Brightness Sensing Type	Analog wall-mounted cell
Control Type	By brightness detection
Market Segment	Residential Small commercial
Compatibility Code	IC2000

Environment

Ambient Air Temperature For Operation	-25...50 °C
Ip Degree Of Protection	IP20 B
Standards	EN 60529 EN 60669

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.6 cm
Package 1 Width	9.4 cm
Package 1 Length	11 cm
Package 1 Weight	299 g

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)