

Product datasheet

Specifications



extension ETL - 1P - 1NO - 32A -
coil 110 VDC - 230...240VAC
50/60Hz

15505

⚠ Discontinued on: 13 Jun 2018

⚠ Discontinued

EAN Code: 3303430155058

Main

Product Or Component Type	Extension for impulse relay
Device Short Name	ETL
Relay Application	Remote control
Poles Description	1P
Pole Contact Composition	1 NO
[In] Rated Current	32 A
Network Type	AC

Complementary

Network Frequency	50/60 Hz
[Ue] Rated Operational Voltage	250 V AC 50/60 Hz
Control Type	Remote control Toggle
Control Signal Type	Impulse
Switching Frequency	5 switching operations/minute
Impulse Duration	50 ms
Remote Control Type	Illuminated push-button
Local Signalling	ON/OFF indication
[Uc] Control Circuit Voltage	230...240 V AC 50/60 Hz 110 V DC
Supply Inrush Power	19 VA
Mounting Mode	Fixed, on right side of TL
Mounting Support	35 mm symmetrical DIN rail
9 Mm Pitches	2
Height	84 mm
Width	18 mm
Depth	60 mm
Colour	Grey
Electrical Durability	AC-21: 50000 cycles AC-22: 20000 cycles
Connections - Terminals	Tunnel type terminals
Auxiliary Connection Terminal	Tunnel type terminalscontrol circuit in 0.5...6 mm ²

Environment

Noise Level	60 dB
Tropicalisation	2
Relative Humidity	95 % at 55 °C
Ambient Air Temperature For Operation	-20...50 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3 cm
Package 1 Width	8 cm
Package 1 Length	8.5 cm
Package 1 Weight	0.12 kg

Contractual warranty

Warranty	18 months
----------	-----------