

# Product datasheet

Specifications



## Miniature circuit-breaker, Acti9 iC60H, 1P, 25 A, C curve, 10000 A (IEC 60898-1), 15 kA (IEC 60947-2)

A9F87125

### Main

Device Application	Distribution
Range	Acti9
Product Name	Acti9 iC60
Product Or Component Type	Miniature circuit-breaker
Device Short Name	iC60H
Poles Description	1P
Number Of Protected Poles	1
[In] Rated Current	25 A
Network Type	AC DC
Trip Unit Technology	Thermal-magnetic
Curve Code	C
Breaking Capacity	10000 A Icn at 230 V AC 50/60 Hz conforming to EN/IEC 60898-1 15 kA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2 42 kA Icu at 12...60 V AC 50/60 Hz conforming to EN/IEC 60947-2 30 kA Icu at 100...133 V AC 50/60 Hz conforming to EN/IEC 60947-2 15 kA Icu at 60...72 V DC conforming to EN/IEC 60947-2 20 kA Icu at 12...60 V DC conforming to EN/IEC 60947-2
Utilisation Category	Category A conforming to EN 60947-2 Category A conforming to IEC 60947-2
Suitability For Isolation	Yes conforming to EN 60898-1 Yes conforming to EN 60947-2 Yes conforming to IEC 60898-1 Yes conforming to IEC 60947-2
Standards	IEC 60898-1 EN 60898-1 IEC 60947-2 EN 60947-2

### Complementary

Network Frequency	50/60 Hz
Magnetic Tripping Limit	8 x In +/- 20 %

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>[Ics] Rated Service Breaking Capacity</b>	21 kA 50 % conforming to EN 60947-2 - 12...60 V AC 50/60 Hz 7.5 kA 50 % conforming to EN 60947-2 - 220...240 V AC 50/60 Hz 21 kA 50 % conforming to IEC 60947-2 - 12...60 V AC 50/60 Hz 7.5 kA 50 % conforming to IEC 60947-2 - 220...240 V AC 50/60 Hz 7500 A 75 % conforming to EN 60898-1 - 230 V AC 50/60 Hz 7500 A 75 % conforming to IEC 60898-1 - 230 V AC 50/60 Hz 15 kA 50 % conforming to IEC 60947-2 - 100...133 V AC 50/60 Hz 15 kA 50 % conforming to EN 60947-2 - 100...133 V AC 50/60 Hz 15 kA 100 % conforming to EN 60947-2 - 72 V DC 15 kA 100 % conforming to IEC 60947-2 - 72 V DC 20 kA 100 % conforming to EN 60947-2 - 12...60 V DC 20 kA 100 % conforming to IEC 60947-2 - 12...60 V DC
<b>Limitation Class</b>	3 conforming to EN 60898-1 3 conforming to IEC 60898-1
<b>[Ui] Rated Insulation Voltage</b>	500 V AC 50/60 Hz conforming to EN 60947-2 500 V AC 50/60 Hz conforming to IEC 60947-2
<b>[Uimp] Rated Impulse Withstand Voltage</b>	6 kV conforming to EN 60947-2 6 kV conforming to IEC 60947-2
<b>Contact Position Indicator</b>	Yes
<b>Control Type</b>	Toggle
<b>Local Signalling</b>	Trip indicator
<b>Mounting Mode</b>	Fixed
<b>Mounting Support</b>	DIN rail
<b>Comb Busbar And Distribution Block Compatibility</b>	Top or bottom: YES
<b>9 Mm Pitches</b>	2
<b>Height</b>	85 mm
<b>Width</b>	18 mm
<b>Depth</b>	78.5 mm
<b>Net Weight</b>	0.215 kg
<b>Colour</b>	White
<b>Mechanical Durability</b>	20000 cycles
<b>Electrical Durability</b>	10000 cycles
<b>Connections - Terminals</b>	Single terminal (top or bottom) 1...25 mm <sup>2</sup> rigid Single terminal (top or bottom) 1...16 mm <sup>2</sup> flexible
<b>Wire Stripping Length</b>	14 mm for top or bottom connection
<b>Tightening Torque</b>	2 N.m top or bottom
<b>Earth-Leakage Protection</b>	Without

## Environment

<b>Ip Degree Of Protection</b>	IP20 conforming to IEC 60529 IP20 conforming to EN 60529
<b>Pollution Degree</b>	3 conforming to EN 60947-2 3 conforming to IEC 60947-2
<b>Overvoltage Category</b>	IV
<b>Tropicalisation</b>	2 conforming to IEC 60068-1
<b>Relative Humidity</b>	95 % at 55 °C
<b>Operating Altitude</b>	0...2000 m
<b>Ambient Air Temperature For Operation</b>	-35...70 °C
<b>Ambient Air Temperature For Storage</b>	-40...85 °C

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.800 cm
Package 1 Width	7.200 cm
Package 1 Length	9.200 cm
Package 1 Weight	116.000 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	12
Package 2 Height	8.200 cm
Package 2 Width	9.800 cm
Package 2 Length	22.200 cm
Package 2 Weight	1.474 kg
Unit Type Of Package 3	S03
Number Of Units In Package 3	132
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	16.701 kg

## Contractual warranty

Warranty	18 months
----------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

Halogen Free Product

## Certifications & Standards

Reach Regulation	<a href="#">REACH Declaration</a>
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations