

Product datasheet

Specifications



EasyLogic - Digital Panel Meter DM3000 - Ampermeter - three phases

METSEDM3110

Main

Range	EasyLogic
Product Name	EasyLogic DM3000
Device Short Name	DM3110
Product Or Component Type	Ammeter
Device Application	Load control Test laboratories GenSet

Complementary

Poles Description	3P + N 3P
Type Of Measurement	Current
[Us] Rated Supply Voltage	100...230 V AC +/- 20 % 100...230 V DC +/- 20 %
Supply Frequency	50/60 Hz +/- 5 Hz
Network Frequency	60 Hz 50 Hz
Maximum Power Consumption In Va	3 VA at 230 V AC
Display Type	LED
Display Digits	4
Full Scale Display	999.9
Control Type	Selector switch built-in
Analogue Input Type	Current 0...5 Athree phase
Measurement Current	1/5 A, 50...6000 mA AC, 50/60 Hz +/- 5 Hz
Accuracy	Current +/- 0.5 % of full scale for class 0.5
Device Mounting	Flush
Mounting Support	Panel
Type Of Installation	Indoor
Measurement Category	Category III
Standards	IEC 61326
Product Certifications	CE conforming to IEC 61010-1

Environment

Electromagnetic Compatibility	Conducted and radiated emissions class A conforming to CISPR 11 Electrostatic discharge conforming to IEC 61000-4-2 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Surge immunity test conforming to IEC 61000-4-5 Conducted RF disturbances conforming to IEC 61000-4-6 Magnetic field at power frequency conforming to IEC 61000-4-8 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11 Harmonics conforming to IEC 61000-3-2 Limitation of voltage changes, voltage fluctuations and flicker in low-voltage conforming to IEC 61000-3-3
Ip Degree Of Protection	Front panel: IP50 Body: IP30
Relative Humidity	5...95 %
Pollution Degree	2
Ambient Air Temperature For Operation	-10...60 °C
Ambient Air Temperature For Storage	-25...70 °C
Colour	Black
Width	96 mm
Height	96 mm
Depth	38 mm
Cut-Out Dimensions	92 x 92 mm
Net Weight	220 g

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.6 cm
Package 1 Width	9.6 cm
Package 1 Length	4.35 cm
Package 1 Weight	304 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	16
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	4.9 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	128
Package 3 Height	105 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	39 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)