

# Product data sheet

Specifications



## CONTACTOR LATCH BLOCK IEC

LA6DK20M

**Product availability: Non-Stock - Not normally stocked in distribution facility**

**Price\*: 92.40 USD**

### Main

Range	TeSys
Product or Component Type	Mechanical latch block
Product compatibility	LC1D80...D150 3 phase AC LC1D80 3 phase DC LC1D150 3 phase DC LC1D80 3 phases + neutral AC LC1D115 3 phases + neutral AC LP1D80 3 phases + neutral DC LC1D115 3 phases + neutral DC
[Uc] control circuit voltage	220/240 V AC 50/60 Hz 220/240 V DC

### Complementary

mounting location	Front side
Tripping control	Manual Electrical
[Ui] rated insulation voltage	690 V IEC 60947-5-1
Power required in VA	25 AC
Power required in W	30 W DC
Mechanical durability	500000 cycles
Maximum operating rate	1200 cyc/h
On-load factor	10 %
Net Weight	0.20 lb(US) (0.09 kg)

### Environment

Product Certifications	CSA UL
IP degree of protection	IP2XIEC 60529
Protective treatment	THIEC 60068
Ambient Air Temperature for Operation	-13.0000000000...131.0000000000 °F (-25...55 °C)
Ambient Air Temperature for Storage	-40.0000000000...176.0000000000 °F (-40...80 °C)

### Ordering and shipping details

Category	US10I1222341
Discount Schedule	0112
GTIN	3389110745894

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Returnability	No
---------------	----

---

Country of origin	FR
-------------------	----

---

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	1.9 in (4.7 cm)
------------------	-----------------

---

Package 1 Width	2.1 in (5.4 cm)
-----------------	-----------------

---

Package 1 Length	2.6 in (6.5 cm)
------------------	-----------------

---

Package 1 Weight	3.4 oz (97.0 g)
------------------	-----------------

---

Unit Type of Package 2	S01
------------------------	-----

---

Number of Units in Package 2	32
------------------------------	----

---

Package 2 Height	5.9 in (15.0 cm)
------------------	------------------

---

Package 2 Width	5.9 in (15.0 cm)
-----------------	------------------

---

Package 2 Length	15.7 in (40.0 cm)
------------------	-------------------

---

Package 2 Weight	7.370 lb(US) (3.343 kg)
------------------	-------------------------

---

## Contractual warranty

---

Warranty	18 months
----------	-----------

---

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)