


Product datasheet

Specifications



PratiKa industrial socket - 63 A - 3P + N + E - 380...415 V AC - IP67

81283

Main

| | |
|---------------------------|---------------|
| Range | Mureva |
| Product or component type | Socket |
| Device short name | Mureva socket |
| Plug, socket category | Low voltage |
| poles description | 3P + N + E |
| Network type | AC |
| Outlet standard | Industrial |

Complementary

| | |
|-------------------------------------|---|
| Mounting mode | Panel-mounted |
| Plug, socket, control station shape | Angled |
| [In] rated current | 63 A |
| [Ue] rated operational voltage | 380...415 V |
| Network frequency | 50/60 Hz |
| ground lug clockwise position | 6 h |
| Plug, socket material | Housing: self-extinguishing engineering polymer |
| Contacts material | Pins: stainless steel Sleeves: nickel plated brass Springs: stainless steel |
| Connections - terminals | Captive screws, completely loosened |
| Cable cross section | 6...25 mm ² |
| Net weight | 0.52 kg |
| Base dimension | 100 x 107 mm |
| Height | 107 mm |
| Width | 100 mm |
| Depth | 129 mm |
| Colour | Grey (RAL 7035) |
| Voltage colour | Red |

Environment

| | |
|-------------------------|------------------------------|
| Standards | EN 60309-1 EN 60309-2 |
| IP degree of protection | IP67 conforming to IEC 60529 |

| | |
|--|---|
| IK degree of protection | IK08 conforming to EN 62262 |
| Fire resistance | 850 °C conforming to IEC 60695-2-11 |
| Relative humidity | 50 % at 40 °C 70 % at 30 °C 90 % at 20 °C |
| Ambient air temperature for operation | 35 °C (86400 s) |

Packing Units

| | |
|-------------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 11.8 cm |
| Package 1 Width | 12.0 cm |
| Package 1 Length | 12.9 cm |
| Package 1 Weight | 530.0 g |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 15 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 8.437 kg |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

RoHS Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu RoHS Directive Pro-active compliance (Product out of EU RoHS legal scope)

China RoHS Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations